



Intermec

Product Profile

- Heavy-duty radomes of high strength pulltruded fiberglass
- Rigid matching network and circuit boards
- Stainless steel mounting hardware



IA36A INTELLITAG™ RUGGED ANTENNA

Joining the diversified line of RFID readers are the Intermec Intellitag RFID antennas. The Intellitag RFID antenna family offers a variety of gain, polarization and radiation pattern options. This antenna is specifically designed for vehicle mount applica-

tions where shock and vibration can far exceed the specifications of antennas designed for fixed applications. Its pulltruded fiberglass radome makes it one of the toughest antennas on the market.

Intermec

Description

868, 6dBi, Vert Pol, N

Frequency Range

865-928 MHz

Gain

6 dBi

Impedance

50 Ohms

VSWR

<1.5:1

Axial Ratio

N/A

Polarization

Vertical

Front-to-Back Ratio

>20 dB

Maximum Input Power

100 Watts (at 50°C)

H-Plane Beamwidth

90 degrees (half power)

E-Plane Beamwidth

70 degrees (half power)

Connector

N

Cable Length

N/A

Weight

1496.8 grams (52.8 oz)

Dimensions

26.1 x 15.4 x 4.8 cm (10.3 x 6.1 x 1.9 in)


Mounting Hardware

203-734-001 kit included

203-733-001 kit order separately

203-735-001 order separately

203-737-001 order separately



Intermec®
expect MORE®

Copyright © 2005 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A.
611684-01A 10/05

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

ADC distribution